848C1B93A0 (611)

ZENOAH
KOMATSU

CE

GB

OWNER'S MANUAL

CHAIN SAWS

G2500

G2500 OPS
(One-Push-Start)

⚠ WARNING ⚠

Before using our products, please read this manual carefully to understand the proper use of your unit.

EXPLANATION OF SYMBOLS AND SAFETY WARNINGS

Read operator's instruction book before operating this machine.

Use the chain saw with two hands.

Read, understand and follow all warnings.

Never touch hot surface.

Wear head, eye and ear protection.

Warning! Danger of kickback.

Use appropriate protections for foot-leg and hand-arm.



This saw is for trained tree service operators only.

WARNING!!!

RISK OF DAMAGING HEARING

IN NORMAL CONDITIONS OF USE, THIS MACHINE
MAY INVOLVE A DAILY LEVEL OF PERSONAL EXPOSURE TO NOISE
FOR THE OPERATOR EQUAL TO OR GREATER THAN

85 dB(A)

MODEL		SOUND LEVEL		VIBRATION LEVEL	
		EN 608-ISO 7182	2000/14/EC	EN608-ISO 7505	
		LpA	LwA guaranteed	Front handle	Rear handle
G2500	25.4 cm^3	97.4 dB(A)	110 dB(A)	4.3 m/s^2	7.0 m/s^2
G2500 OPS	25.4 cm^3	96.5 dB(A)	112 dB(A)	6.2 m/s^2	5.1 m/s^2

APPROVAL NUMBER OF CE EXHAUST EMISSION REGULATION (2002/88/EC)
e13*97/68SH2G3*2002/88*0085*02

DECLARATION OF CONFORMITY TO MACHINES DIRECTIVE

(Directive 98/37/EC, 89/336/EEC)
and to the regulations governing transposition
Internal control production

MANUFACTURER : KOMATSU ZENOAH
No. 9, 1-Chome
MINAMIDAI, KAWAGOE City
SAITAMA, JAPAN

DECLARES THAT THE DESIGN OF THE MACHINE DESCRIBED BELOW :

Model : G2500
Serial no. : 110001 and up
Make : KOMATSU ZENOAH

CONFORMS TO THE REQUIRMENTS OF THE MODIFIED MACHINES DIRECTIVE (Directive 98/37/EC) AND TO THE NATIONAL REGULATIONS GOVERNING ITS TRANSPOSITION ABROAD : AND

THAT IT HAS BEEN ISSUED WITH A "CE" CERTIFICATE,
NO. M. 0303. 02. 2737
BY THE ISTITUTO CERTIFICAZIONE EUROPEA PALAZZO DEL VESCOVO - V. GARIBALDI, 20 40011 ANZOLA DELL' EMILIA - ITALY

Signed in Saitama, Japan **1st September 2001**

Isamu NAKAZATO
General Manager, Quality Assurance Department

DECLARATION OF CONFORMITY TO MACHINES DIRECTIVE

(Directive 98/37/EC, 89/336/EEC)
and to the regulations governing transposition
Internal control production

MANUFACTURER : KOMATSU ZENOAH
No. 9, 1-Chome
MINAMIDAI, KAWAGOE City
SAITAMA, JAPAN

DECLARES THAT THE DESIGN OF THE MACHINE DESCRIBED BELOW :

Model : G2500 OPS
Serial no. : 510001 and up
Make : KOMATSU ZENOAH

CONFORMS TO THE REQUIRMENTS OF THE MODIFIED MACHINES DIRECTIVE (Directive 98/37/EC) AND TO THE NATIONAL REGULATIONS GOVERNING ITS TRANSPOSITION ABROAD : AND

THAT IT HAS BEEN ISSUED WITH A "CE" CERTIFICATE, NO. U3 2592658 01
BY TÜV Rheinland Group - TÜV Rheinland InterCert kft. Product Certification - H-1061 Budapest Paulay Ede u. 52 - HUNGARY

Signed in Saitama, Japan **1st December 2005**

Hitoshi OGATA
General Manager, Quality Assurance Department

Contents

1. For Safe Operation 4
2. Explanation of Symbols on the Machine 8
3. Installing Guide Bar and Saw Chain 9
4. Fuel and Chain Oil 10
5. Operating the Engine 11
6. Sawing 13
7. Maintenance 15
8. Maintenance of Saw Chain and Guide Bar 16
9. Troubleshooting Guide 17
10. Specifications 18
11. Limited Warranty 19

1. For safe operation

⚠ WARNING

This chainsaw has been especially designed for tree maintenance and should therefore only be used by trained operators when working on trees.



1. Never operate a chain saw when you are fatigued, ill, or upset, or under the influence of medication that may make you drowsy, or if you are under the influence of alcohol or drugs.
2. Use safety footwear, snug fitting clothing and eye, hearing and head protection devices.
   Use the vibration-proof glove.
3. Keep the saw chain sharp and the saw, including the AV system, well maintained. A dull chain will increase cutting time, and pressing a dull chain through wood will increase the vibrations transmitted to your hands. A saw with loose components or with damaged or worn AV buffers will also tend to have higher vibration levels.
4. All the above mentioned precautions do not guarantee that you will not sustain whitefinger disease or carpal tunnel syndrome. Therefore, continual and regular users should monitor closely the condition of their hands and fingers.
   If any of the above symptoms appear, seek medical advice immediately.

5. Always use caution when handling fuel. Wipe up all spills and then move the chain saw at least 3 m from the fueling point before starting the engine.

6. Eliminate all sources of sparks or flame (i.e. smoking, open flames, or work that can cause sparks) in the areas where fuel is mixed, poured, or stored.
7. Do not smoke while handling fuel or while operating the chain saw.



8. Do not allow other persons to be near the chain saw when starting or cutting. Keep bystanders and animals out of the work area. Children, pets and bystanders should be a minimum of 10 m away when you start or operate the chain saw.



9. Never start cutting until you have a clear work area, secure footing, and a planned retreat path from the falling tree.

10. Always hold the chain saw firmly with both hands when the engine is running. Use a firm grip with thumb and fingers encircling the chain saw handles.



11. Keep all parts of your body away from the saw chain when the engine is running.



12. Before you start the engine, make sure the saw chain is not contacting anything.
13. This product is provided with a centrifugal clutch. Accordingly, the saw chain starts to rotate the moment the choke knob is set to the “START” position (first step) to start the engine. At the start, put the machine body on the flat ground and pull the starter rope while holding the machine body securely so that the saw chain cannot touch the ground and surrounding obstacles.
14. Don’t pull the starter rope while pulling the throttle lever (“Start while pulling”) in the status where the chain saw is hung with one hand.
    Doing this operation is strictly prohibited.
15. If the saw chain continues to rotate, stop the engine, and then readjust the idle adjustment screw after confirming that there is no hitch on the throttle lever motion.
16. Always carry the chain saw with the engine stopped, the guide bar and saw chain to the rear, and the muffler away from your body.

17. Always inspect the chain saw before each use for worn, loose, or damaged parts. Never operate a chain saw that is damaged, improperly adjusted, or is not completely and securely assembled. Be sure that the saw chain stops moving when the throttle control trigger is released.

18. All chain saw service, other than the items listed in the Owner's Manual, should be performed by competent chain saw service personnel. (E.g., if improper tools are used to remove the flywheel, or if an improper tool is used to hold the flywheel in order to remove the clutch, structural damage to the flywheel could occur which could subsequently cause the flywheel to disintegrate.)

19. Always shut off the engine before setting it down.
20. Use extreme caution when cutting small size brush and saplings because slender material may catch the saw chain and be whipped toward you or pull you off balance.
21. When cutting a limb that is under tension, be alert for springback so that you will not be struck when the tension in the wood fibers is released.

22. Never cut in high wind, bad weather, when visibility is poor or in very high or low temperatures. Always check the tree for dead branches which could fall during the felling operation.

23. Keep the handles dry, clean and free of oil or fuel mixture.
24. Operate the chain saw only in well ventilated areas. Never start or run the engine inside a closed room or building. Exhaust fumes contain dangerous carbon monoxide.

25. Do not operate the chain saw in a tree unless specially trained to do so.
26. Guard against kickback. Kickback is the upward motion of the guide bar which occurs when the saw chain at the nose of the guide bar contacts an object. Kickback can lead to dangerous loss of control of the chain saw.



27. When transporting your chain saw, make sure the appropriate guide bar scabbard is in place.



28. Never touch the muffler guard, guide bar or saw chain with bare hands while the engine is in operation or immediately after shutting down the engine. Doing so could result in serious burns because of high temperature.

(1) muffler guard
(2) guide bar
(3) saw chain

KICKBACK SAFETY PRECAUTIONS FOR CHAIN SAW USERS

⚠ WARNING

- Kickback may occur when the nose or tip of the guide bar touches an object, or when the wood closes in and pinches the saw chain in the cut. Tip contact in some cases may cause a lightning fast reverse reaction,kicking the guide bar up and back to wards the operator. Pinching the saw chain along the top of the guide bar may push the guide bar rapidly back towards the operator. Either of these reactions may cause you to lose control of the saw, which could result in serious personal injury.
- Do not rely exclusively on the safety devices built into your saw. As a chain saw user you should take several steps to keep cutting jobs free from accident or injury.

(1) With a basic understanding of kickback you can reduce or eliminate the element of surprise. Sudden surprise contributes to accidents.

(2) Keep a good grip on the saw with both hands, the right hand on the rear handle, and the left hand on the front handle, when the engine is running. Use a firm grip with thumbs and fingers encircling the chain saw handles. A firm grip will help you reduce kickback and maintain control of the saw.

(3) Make certain that the area in which you are cutting is free from obstructions. Do not let the nose of the guide bar contact a log, branch, or any other obstruction which could be hit while you are operating the saw.

(4) Cut at high engine speeds.

(5) Do not overreach or cut above shoulder height.

(6) Follow the manufacturer's sharpening and maintenance instructions for the saw chain.

(7) Only use replacement bars and chains specified by the manufacturer or the equivalent.

WORKING WITH TREE SERVICE CHAIN-SAWS FROM A ROPE AND HARNESS

This chapter sets out working practices to reduce the risk of injury from tree service chainsaws when working at height from a rope and harness. While it may form the basis of guidance and training literature, it should not be regarded as a substitute for formal training.

General requirements working at height

Operators of tree service chainsaws working at height from a rope and harness should never work alone. A competent ground worker trained in appropriate emergency procedures should assist them.

Operators of tree service chainsaws for this work should be trained in general safe climbing and work positioning techniques and shall properly equipped with harnesses, ropes, strops, karabiners and other equipment for maintaining secure and safe working positions for both themselves and the saw.

Preparing to use the saw in the tree

The chainsaw should checked, fuelled, started and warmed up by the ground worker before it is sent up to the operator in the tree. The chainsaw should be fitted with a suitable strop for attaching to the operator's harness:



a) choke the strop around the attachment point on the rear of the saw (A);



b) provide suitable karabiners to allow indirect (i.e. via the strop) and direct attachment (i.e. at the attachment point on the saw) of saw to the operators harness;
c) ensure the saw is securely attached when it is being sent up to the operator;
d) ensure the saw it secured to the harness before it is disconnected from the means of ascent.

The saw should only be attached to the recommended attachment points on the harness. These may be at mid-point (front or rear) or at the sides. Where possible attaching the saw to centre rear mid-point will keep it clear of climbing lines and support its weight centrally down the operator's spine.



When moving the saw from any attachment point to another, operators should ensure it is secured in the new position before releasing it from the previous attachment point.

Using the chainsaw in the tree

An analysis of accidents with these saws during tree service operations shows the primary cause as being inappropriate one-handed use of the saw. In the vast majority of accidents, operators fail to adopt a secure work position witch allows them to hold both handles of the saw. This results in an increased risk of injury due to:

- not having a firm grip on the saw if it kicks back;
- a lack of control of the saw such that it is more liable to contact climbing lines and operators body (particularly the left hand and arm)
- losing control from insecure work position resulting in contact with the saw (unexpected movement during operation of the saw)

Securing the work position for two-handed use

To allow the operator to hold the saw with both hands, they should as general rule, aim for secure work position where they are operating the saw at:

- hip level when cutting horizontal sections;
- solar plexus level when cutting vertical sections.

Where the operator is working close into vertical stems with a low lateral forces on their work position, then a good footing may be all that is needed to maintain a secure work position. However as operators move away from the stem, they will need to take steps to remove or counteract the increasing lateral forces by, for example, a re-direct of the main line via a supplementary anchor point or using an adjustable strop direct from the harness to a supplementary anchor point.



Gaining a good footing at the working position can be assisted by use of a temporary foot stirrup created from an endless sling.



Starting the saw in the tree

When starting the saw in the tree, the operator should:

a) apply the chain brake before starting;
b) hold saw on either the left or right of the body when starting:

1) on the left side hold the saw with either the left hand on the front handle or the right hand on the rear handle and thrust the saw away from the body while holding the pull starter cord in the other hand;
2) on the right side, hold the saw with the right hand on either handle and thrust the saw away from the body while holding the pull starter cord in the left hand.

The chain brake should always be engaged before lowering a running saw onto its strop.
Operators should always check the saw has sufficient fuel before undertaking critical cuts.

One-hand use of the chainsaw

Operators should not use tree service chainsaws one-handed in place of unstable work positioning or in preference to a handsaw when cutting small diameter wood at the branch tips.
Tree service chainsaws should only be used one-handed where:

- the operator cannot gain a work position enabling two-handed use; and
- they need to support their working position with one hand; and
- the saw is being used at full stretch, at right angles to and out of line with the operator's body.

Operators should never:

- cut with the kickback zone at the tip of the chainsaw guide bar
- 'hold and cut' sections
- attempt to catch falling sections.

Freeing a trapped saw

If the saw should become trapped during cutting, operators should:

- switch off the saw and attach it securely to the tree inboard (i.e. towards the truck side) of the cut or to a separate tool line;
- pull the saw from the kerf whilst lifting the branch as necessary;
- if necessary, use a handsaw or second chain saw to release the trapped saw by cutting a minimum of 30 cm away from the trapped saw.

Whether a handsaw or a chainsaw is used to free a stuck saw, the release cuts should always be outboard (toward the tips of the branch), in order to prevent the saw being taken with the section and further complicating the situation.

2. Explanation of Symbols on the Machine

⚠ WARNING For safe operation and maintenance, symbols are carved in relief on the machine. According to these indications, please be careful not to make any mistake.

The port to refuel “MIX GASOLINE”
Position: Fuel cap

The port to top up chain oil
Position: Oil cap



Setting the switch to the “O” position, the engine stops immediately.
Position: Front at the top of the rear handle

Starting the engine. If you pull out the choke knob (at the back-right of the rear handle) to the point of the arrow, you can set the starting mode as follows:
• *First-stage position – starting mode when the engine is warm.*
• *Second-stage position – starting mode when the engine is cold.*
Position: Upper-right of the aircleaner cover



The screw under the “H” stamp is The High-speed adjustment screw.
The screw under the “L” stamp is The Slow-speed adjustment screw.
The screw at the left of the “T” stamp is the Idle adjustment screw.
Position: Left side of the rear handle



Shows the directions that the chain brake is released (white arrow) and activated (black arrow).
Position: Front of the chain cover

If you turn the rod by screwdriver follow the arrow to the "MAX" position, the chain oil flow more, and if you turn to the "MIN" position, less.
Position: Bottom of the power unit



<G2500 One-push-start only>
A : Indicates the operation selecting position of the select lever for the One-push-start and Super e-START at a start of the recoil.

B : Indicates the operating direction of the select lever at a start of the engine by One-push-start.
Position: Upper side portion of the recoil starter

3. Installing Guide Bar and Saw Chain

A standard saw unit package contains the items as illustrated.



Open the box and install the guide bar and the saw chain on the power unit as follows:

⚠ WARNING

The saw chain has very sharp edges. Use thick protective gloves for safety.

1. Pull the guard towards the front handle to check that the chain brake is not engaged.
2. Loosen the nuts and remove the chain cover.
3. Fix the hanger on the rear of power unit by screw.



4. Mount the guide bar then fit the saw chain around the bar and sprocket.



NOTE

Pay attention to the correct direction of the saw chain.



5. Fit the chain tensioner nut into the lower hole of the guide bar, then install the chain cover, and fasten the mounting nut to finger tightness.



⚠ WARNING

When installing the chain cover, be sure to fit the hook completely at the rear end of the cover.

6. While holding up the tip of the bar, adjust the chain tension by turning the tensioner screw until the tie straps just touch the bottom side of the bar rail.



7. Tighten the nuts securely with the bar tip held up (11.8-14.7 N.m./120-150 kg-cm). Then check the chain for smooth rotation and proper tension while moving it by hand. If necessary, readjust with the chain cover loose.



8. Tighten the tensioner screw.

⚠ WARNING

A new chain will expand its length in the beginning of use. Check and readjust the tension frequently as a loose chain can easily derail or cause rapid wear of itseif and the guide bar.

4. Fuel and Chain Oil

■ FUEL

⚠ WARNING

- **Gasoline is very flammable. Avoid smoking or bringing any flame or sparks near fuel. Make sure to stop the engine and allow it cool before refueling the unit. Select outdoor bare ground for fueling and move at least 3 m (10 ft) away from the fueling point before starting the engine.**

- The Komatsu Zenoah engines are lubricated by oil specially formulated for air-cooled 2-cycle gasoline engine use. If Komatsu Zenoah oil is not available, use an anti-oxidant added quality oil expressly labeled for air-cooled 2-cycle engine use (JASO FC GRADE OIL or ISO EGC GRADE).
- Do not use BIA or TCW (2-stroke water-cooling type) mixed oil.

■ RECOMMENDED MIXING RATIO
GASOLINE 50 : OIL 1
<when using ZENOAH genuine oil>

- **Exhaust emission are controlled by the fundamental engine parameters and components (eq., carburation, ignition timing and port timing) without addition of any major hardware or the introduction of an inert material during combustion.**
- These engines are certified to operate on unleaded gasoline.
- Make sure to use gasoline with a minimum octane number of 89RON (USA/Canada: 87AL).
- If you use a gasoline of a lower octane value than prescribed, there is a danger that the engine temperature may rise and an engine problem such as piston seizing may consequently occur.
- Unleaded gasoline is recommended to reduce the contamination of the air for the sake of your health and the environment.
- Poor quality gasolines or oils may damage sealing rings, fuel lines or fuel tank of the engine.

■ HOW TO MIX FUEL

⚠ WARNING

- Pay attention to agitation.

1. Measure out the quantities of gasoline and oil to be mixed.
2. Put some of the gasoline into a clean, approved fuel container.
3. Pour in all of the oil and agitate well.
4. Pour in the rest of gasoline and agitate again for at least one minute. As some oils may be difficult to agitate depending on oil ingredients, sufficient agitation is necessary for the engine to last long. Be careful that, if the agitation is insufficient, there is an increased danger of early piston seizing due to abnormally lean mixture.
5. Put a clear indication on the outside of the container to avoid mixing up with gasoline or other containers.
6. Indicate the contents on outside of container for easy identification.

■ FUELING THE UNIT

1. Untwist and remove the fuel cap. Rest the cap on a dustless place.
2. Put fuel into the fuel tank to 80% of the full capacity.
3. Fasten the fuel cap securely and wipe up any fuel spillage around the unit.

⚠ WARNING

1. Select bare ground for fueling.
2. Move at least 10 feet (3 meters) away from the fueling point before starting the engine.
3. Stop the engine before refueling the unit. At that time, be sure to sufficiently agitate the mixed gasoline in the container.

■ FOR YOUR ENGINE LIFE, AVOID:

1. FUEL WITH NO OIL (RAW GASOLINE) – It will cause severe damage to the internal engine parts very quickly.
2. GASOHOL – It can cause deterioration of rubber and/or plastic parts and disruption of engine lubrication.
3. OIL FOR 4-CYCLE ENGINE USE – It can cause spark plug fouling, exhaust port blocking, or piston ring sticking.
4. **Mixed fuels which have been left unused for a period of one month or more** may clog the carburetor and result in the engine failing to operate properly.
5. In the case of storing the product for a long period of time, clean the fuel tank after rendering it empty. Next, activate the engine and empty the carburetor of the composite fuel.
6. In the case of scrapping the used mixed oil container, scrap it only at an authorized repository site.

NOTE

As for details of quality assurance, read the description in the section Limited Warranty carefully. Moreover, normal wear and change in product with no functional influence are not covered by the warranty. Also, be careful that, if the usage in the instruction manual is not observed as to the mixed gasoline, etc. described therein, it may not be covered by the warranty.

■ CHAIN OIL

Use motor oil SAE #10W-30 all year round or SAE #30 ~ #40 in summer and SAE #20 in winter.



NOTE

Do not use wasted or regenerated oil that can cause damage to the oil pump.

5. Operating the Engine

⚠ WARNING

It is very dangerous to run a chainsaw that mounts broken parts or lacks any parts.
Before starting engine, make sure that all the parts including bar and chain are installed properly.

■ STARTING THE ENGINE

Normal start

1. Fill fuel and chain oil tanks respectively, and tighten the caps securely.



2. Continuously push the priming bulb until fuel comes in the bulb.



3. Set the switch to “I” position.



(G2500 OPS)

- Move the select lever to the machine back side indicated by label until it is stopped, and then set this lever to the recoil start mode.



4. Pull out the choke knob to the second-stage position. The choke will close and the throttle lever will then be set in the starting position.



NOTE

When restarting immediately after stopping the engine, set the Choke knob in the first-stage position (choke open and throttle lever in the starting position).
Once the choke knob has been pulled out, it will not return to the operating position even if you press down on it with your finger. When you wish to return the choke knob to the operating position, pull out the throttle lever instead.

5. While holding the saw unit securely on the ground, pull the starter rope vigorously.



⚠ WARNING

Do not start the engine while the chain saw hangs in one hand. The saw chain may touch your body. This in very dangerous.

6. When engine has ignited, first push in the choke knob to the first-stage position and then pull the starter again to start the engine.
7. Allow the engine to warm up with the throttle lever pulled slightly.

One-push-start

(G2500 OPS only)

⚠ WARNING

- Use One-push-start after performing warming-up by Recoil Start in the status where the machine body is securely fixed. You can not use OPS when the engine is cold.
- The starting performance of the engine depends on the adjustment of the engine. Ask the distributor to adjust the engine if possible.
- Be careful not to set OPS in motion except when starting the engine. If so, it may lead to serious injury.

1. Move the select lever to the front side of the machine body indicated by label until it is stopped, and set this lever to the One-push-start mode.



2. Put the machine body on the stable ground and make sure that there is no obstacle around the saw-crossing portion. Then, while holding the front handle with the left hand and putting the right foot on the frame portion, pull out the starter rope slowly.



NOTE

The rope may be pulled out little by little several times.

⚠ WARNING

- When pulling out the rope, large clanging is produced. With this clanging, stop pulling out the rope at once. This sound notifies that One-push-start has been set.
- Don't pull out the rope excessively or don't pull it out without load by the starter only, otherwise a starter failure will occur.

3. Before starting the engine, fix the engine securely and make sure that there is no obstacle around the saw chain. Then, push the top of the engine stop switch on the right side of the rear handle and set it to the "Run" position. After that, move the select lever to the rear side of the machine body indicated by label. The starter is started to start the engine.



NOTE

If the engine cannot be started by the above procedure, repeat the above operations again. If the engine cannot be started smoothly, it may be necessary to add warming-up or readjust the engine. Perform warming-up enough and ask the distributor to readjust the engine.

■ FOR SMOOTHER USE OF ONE-PUSH-START

To use One-push-start more smoothly, it is important to perform warming-up longer than ever.

1. When the outside temperature is 0° or more, perform warming-up for about 5 seconds with the throttle fully opened. And leave the product for 5 minutes or less after the engine stops. Then, use the product. With this, the engine can be started more securely.
2. When the outside temperature is below 0°C, repeat the above warming-up operation twice or more. After the engine stops, use the product in a shorter leaving time.

⚠ WARNING

- Be sure to perform warming-up with the guide bar and the saw chain mounted.
- Keep clear of the saw chain as it will start rotatIng upon starting of engine.
- Before you start the engine, make sure the saw chain is not contacting anything.

■ CHECKING THE OIL SUPPLY

⚠ WARNING

Make sure to set up the bar and the chain when checking the oil supply.
If not, the rotating parts may be exposed. It is very dangerous.

After starting the engine, run the chain at medium speed and see if chain oil is scattered off as shown in the figure.

The chain oil flow can be changed by inserting a screwdriver in the hole on bottom of the clutch side. Adjust according to your work conditions.



The oil tank should become nearly empty by the time fuel is used up. Be sure to refill the oil tank every time when refueling the saw.

■ ADJUSTING THE CARBURETOR



The carburetor on your unit has been factory adjusted, but may require fine tuning due to a change in operating conditions.
Before adjusting the carburetor, make sure that the provided air/fuel filters are clean and fresh and the fuel properly mixed.

When adjusting, take the following steps:

NOTE

Be sure to adjust the carburetor with the bar chain attached.

1. H and L needles are restricted within the number of turn as shown below.

   H needle : -1/4
   L needle : -1/4

2. Start the engine and allow it to warm up in low speed for a few minutes.
3. Turn the idle adjusting screw (T) counterclockwise so that the saw chain does not turn. If the idling speed is too slow, turn the screw clockwise.
4. Make a test cut and adjust the H needle for best cutting power, not for maximum speed.

■ CHAIN BRAKE

The chain brake is a device which stops the chain instantaneously if the chain saw recoils due to kickback. Normally, the brake is activated automatically by inertial force. It can also be activated manually by pushing the brake lever (left-hand guard) down toward the front. When the brake operates, a yellow cone pops up from the base of the brake lever.

Releasing the Brake

Pull the brake lever up toward the left-hand handle until it clicks into place.

⚠ WARNING

- When the brake operates, release the throttle lever to slow down the engine speed. Continuous operation with the brake engaged will generate heat from the clutch and may cause trouble.
- At machine inspection prior to each job, check the operating condition of the brake following the steps.

1. Start the engine and grasp the handle securely with both hands.
2. Pulling the throttle lever to maintain the chain operation, push the brake lever (left-hand guard) down toward the front using the back of your left hand.
3. When the brake operates and the chain is stopped, release the throttle lever.
4. Release the brake.



■ STOPPING THE ENGINE

1. Release the throttle lever to allow the engine to idle for a few minutes.
2. Set the switch to the “O” (STOP) position.



6. Sawing

⚠ WARNING

- Before proceeding to your job, read the section “For Safe Operation”. It is recommended to first practice sawing easy logs. This also helps you get accustomed to your unit.
- Always follow the safety regulations. The chain saw must only be used for cutting wood. It is forbidden to cut other types of material. Vibrations and kickback vary with different materials and the requirements of the safety regulations would not be respected. Do not use the chain saw as a lever for lifting, moving or splitting objects. Do not lock it over fixed stands. It is forbidden to hitch tools or applications to the PTO other than those specified by the manufacturer.
- It is not necessary to force the saw into the cut. Apply only light pressure while running the engine at full throttle.
- When the saw chain is caught in the cut, do not attempt to pull it out by force, but use a wedge or a lever to open the way.

■ GUARD AGAINST KICKBACK



- This saw is equipped with a chain brake that will stop the chain in the event of kickback if operating properly. You must check the chain brake operation before each usage by running the saw at full the throttle for I - 2 seconds and pushing the front hand guard forward. The chain should stop immediately with the engine at full speed. If the chain is slow to stop or does not stop, replace the brake band and clutch drum before use.

- It is extremely important that the chain brake be checked for proper operation before each use and that the chain be sharp in order to maintain the kickback safety level of this saw. Removal of the safety devices, inadequate maintenance, or incorrect replacement of the bar or chain may increase the risk ot serious personal injury due to kickback.

■ FELLING A TREE



1. Decide the felling direction considering the wind, lean of the tree, location of heavy branches, ease of completing the task after felling and other factors.
2. While clearing the area around the tree, arrange a good foothold and retreat path.
3. Make a notch cut one-third of the way into the tree on the felling side.
4. Make a felling cut from the opposite side of the notch and at a level slightly higher than the bottom of the notch.

⚠ WARNING

When you fell a tree, be sure to warn neighboring workers of the danger.

Bucking and Limbing

⚠ WARNING

- Always ensure your foothold. Do not stand on the log.
- Be alert to the rolling over of a cut log. Especially when working on a slope, stand on the uphill side of the log.
- Follow the instructions in “For Safe Operation” to avoid kickback of the saw.

Before starting work, check the direction of bending force inside the log to be cut. Always finish cutting from the opposite side of the bending direction to prevent the guide bar from being caught in the cut.

A log lying on the ground



Saw down halfway, then roll the log over and cut from the opposite side.

A log hanging off the ground



In area A, saw up from the bottom one-third and finish by sawing down from the top. In area B, saw down from the top one-third and finish by sawing up from the bottom.

Cutting the limbs of Fallen Tree



First check to which side the limb is bent. Then make the initial cut from the bent side and finish by sawing from the opposite side.

⚠ WARNING

Be alert to the springing back of a cut limb.

Pruning of Standing Tree



Cut up from the bottom, finish down from the top.

⚠ WARNING

- Do not use an unstable foothold or ladder.
- Do not overreach.
- Do not cut above shoulder height.
- Always use both your hands to hold the saw.

7. Maintenance

⚠ WARNING

Before cleaning, the inspecting or repairing the unit, make sure that engine has stopped and is cool. Disconnect the spark plug to prevent accidental starting.

■ MAINTENANCE AFTER EACH USE

1. Air filter

Loosen the knob and remove the air cleaner cover. Take off the filter elements and tap off attached sawdust. When they are extremely dirty, shakewash with gasoline. Dry them completely before reinstalling.



2. Oiling port

Dismount the guide bar and check the oiling port for clogging.



3. Guide bar

When the guide bar is dismounted, remove sawdust in the bar groove and the oiling port.

<Type : sprocket nose>

Grease the nose sprocket from the feeding port on the tip of the bar.



4. Others

Check for fuel leakage and loose fastenings and damage to major parts, especially handle joints and guide bar mounting. If any defects are found, make sure to have them repaired before operating the saw again.

■ PERIODICAL SERVICE POINTS

1. Cylinder fins

1. Remove the starter case.
2. Remove sawdust between the cylinder fins.
3. Clean the valute area.



2. Fuel filter

(a) Using a wire hook, take out the filter from the filler port.



(b) Wash the filter with gasoline.
Replace with new one if clogged with dirt completely.

⚠ WARNING

When returning the filter, use a pinch not to be folded the suction pipe.

3. Oil filter

1. With a wire hook, take out the oil filter from the feeding port.



2. Wash the filter with gasoline.

⚠ WARNING

When returning the filter, use a pinch not to be folded the suction pipe.

4. Spark plug



Clean the electrodes with a wire brush and reset the gap to 0.6 mm as necessary.

5. Sprocket



Check for cracks and for excessive wear interfering with the chain drive. If the wear is considerable, replace it with new one. Never fit a new chain on a worn sprocket, or a worn chain on a new sprocket.

6. Way of the cooling air

⚠ WARNING

- The engine metal parts can burn your skin. Never touch the cylinder, muffler or ignition plug etc. during operation or right after stopping the engine.
- Before starting the engine, check around the muffler and take off sawdust. If you do not, it will cause the overheating and a fire. For preventing the trouble, please keep clean around the muffler.

This engine is air-cooled. Dust clogging between the inlet port of the cooling air and cylinder fins will cause overheating of the engine. Periodically check and clean the cylinder fins after removing the air cleaner and the cylinder cover.



❗ IMPORTANT

When installing the cylinder cover, make sure that switch wires and grommets are positioned correctly in place.

7. Muffler

⚠ WARNING

If you do not attach the muffler correctly, after engine starts, the muffler will be loosen and the hightemperature exhaust gas spout. After cleaning the muffler, pay attention to fit up the muffler according to the explanation as follows.

1. Muffler body, muffler cover and baffle will be combined correctly.



2. Be sure the gasket is not broken. If it is broken, change to the new one.
3. Before tightening the screw, rub the gross on it.
4. After making a test run, re-tighten the screw (TORQUE: 6.9-7.8 N.m./70-80 kg-cm)

⚠ WARNING

Right after stopping the engine, do not touch the muffler with one's bare hands. It will cause to burn your hands.

If carbon clogs between the muffler, it will cause the poor-output and the trouble in starting. After each 100 hours, check and clean inside the muffler.

8. Recoil Starter

- For recoil maintenance, when attaching or detaching the starter of One-push-start model, the select lever should be in the position of the rear side (G2500 One-push-start only).
- Don't pull the starter when detaching it from the unit. It will cause machine defect or serious injury by touching rotating parts on your body part carelessly.



⚠ WARNING

Don't pull the starter when detaching it from the unit.



8. Maintenance of Saw Chain and Guide Bar

■ Saw Chain

⚠ WARNING

It is very important for smooth and safe operation to always keep the cutters sharp.

The cutters need to be sharpened when:
- Sawdust becomes powder-like.
- You need extra force to saw in.
- The cut path does not go straight.
- Vibration increases.
- Fuel consumption increases.

Cutter setting standards:

⚠ WARNING

Be sure to wear safety gloves.

Before filing:
- Make sure the saw chain is held securely.
- Make sure the engine is stopped.
- Use a round file of proper size for the chain.

Chain type:	91VG / 25AP
File size:	5/32 in (4.0 mm)

Place the file on the cutter and push straight forward. Keep the file position as illustrated.



After each cutter has been filed, check the depth gauge and file it to the proper level as illustrated.



⚠ WARNING

Be sure to round off the front edge to reduce the chance of kickback or tie-strap breakage.

Make sure every cutter has the same length and edge angles as illustrated.



■ **Guide Bar**

- Reverse the bar occasionally to prevent partial wear.
- The bar rail should always be square. Check for wear of the bar rail. Apply a ruler to the bar and the out side of a cutter. If a gap is observed between them, the rail is normal. Otherwise, the bar rail is worn. Such a bar needs to be corrected or replaced.



⚠ WARNING:

This saw is equipped with one of the following low kickback bar/chain combinations:

		Komatsu Zenoah Part Number	
Bar Size	Guide Bar	Saw Chain	Drum
10	2475-52110	2475-52210	2475-51110
10	2475-52120	3622-52210	2841-51110

9. Troubleshooting Guide

Case 1. Starting failure

⚠ WARNING

Make sure the icing prevention system is not working.

Check fuel for water or substandard mixture. → Replace with proper fuel.

↓

Check for engine flooding. → Remove and dry the spark plug. Then pull the starter again with no choke.

↓

Check spark ignition. → Replace with a new plug.

Case 2. Lack of power/Poor acceleration/ Rough idling

Check fuel for water or substandard mixture. → Replace with proper fuel.

↓

Check air filter and fuel filter for clogging. → Clean.

↓

Check carburetor for inadequate adjustment. → Readjust speed needles.

Case 3. Oil does not come out

Check oil for substandard quality. → Replace.

↓

Check oil passage and ports for clogging. → Clean.

If the unit seems to need further service, please consult with an authorized service shop in your area.

10. Specifications

Power unit:
G2500 / G2500 OPS
Displacement (cm^3): 25.4
Fuel: ..... Mixture (Gasoline 50 : Two-cycle oil 1)
Fuel tank capacity (cm^3): 230
Chain oil: ..... Motor oil SAE# 10W-30
Oil tank capacity (cm^3): 160
Carburetor: ..... Diaphragm type
Ignition system:: ..... Solid State
Spark plug: ..... Champion RCJ-7Y
Oil feeding system: ..... Mechanical pump
Max. speed ..... 12,500 (min^{-1})
Idle speed ..... 2,900 (min^{-1})

G2500
Dimensions (L x W x H) (mm): ..... 265 x 220 x 220
Dry weight
Power unit only (kg): 2.9
Power: ..... 0.96/9,000 (kw/min^{-1})

G2500 OPS (One-push-start)
Dimensions (L x W x H) (mm): ..... 265 x 235 x 220
Dry weight
Power unit only (kg): 3.1
Power: ..... 0.88/9,000 (kw/min^{-1})

Cutting head:
<Sprocket bar>
Sprocket: 6T
Chain speed at max. power ..... 17.1 (m/s)
Guide bar
Type: ..... Sprocket nose
Size (in. (cm)): 10 (25)
Saw chain
Type: ..... Oregon 91VG
Pitch (in. (mm)): 3/8 (9.53)
Gauge (in. (mm)): 0.05 (1.27)
<Hard nose bar>
Sprocket: 8T
Chain speed at max. power ..... 15.2 (m/s)
Guide bar
Type: ..... ZENOAH carving (Hard nose)
Size (in. (cm)): 10 (25)
Saw chain
Type: ..... Oregon 25AP
Pitch (in. (mm)): 1/4 (6.35)
Gauge (in. (mm)): 0.05 (1.27)

G2500 series are equipped with Chain Brake.
Specifications are subject to change wihout notice.

11. Limited warranty

Should any failure occur on the product under normal operating conditions within the applicable warranty period, the failed part will be replaced or repaired free of charge by a KOMATSU ZENOAH authorized dealer.

WARRANTY PERIOD: 1 year (6 months if used professionally, and 30 days if used for rental purpose) from the date of initial purchase.

THE PURCHASER SHALL BEAR COSTS OF TRANSPORTING THE UNIT TO AND FROM THE KOMATSU ZENOAH DEALER.

THE PURCHASER SHALL NOT BE CHARGED FOR DIAGNOSTIC LABOR WHICH LEADS TO THE DETERMINATION THAT A WARRANTED PART IS DEFECTIVE, IF THE DIAGNOSTIC WORK IS PERFORMED AT THE KOMATSU ZENOAH DEALER.

THE PURCHASER OR OWNER IS RESPONSIBLE FOR THE PERFORMANCE OF THE REQUIRED MAINTENANCE AS DEFINED BY THE MANUFACTURER IN THE OWNER/OPERATOR MANUAL.

ANY WARRANTED PART WHICH IS NOT SCHEDULED FOR REPLACEMENT AS REQUIRED MAINTENANCE, OR WHICH IS SCHEDULED ONLY FOR REGULAR INSPECTION TO THE EFFECT OF REPAIR OR “REPLACE AS NECESSARY” SHALL BE WARRANTED FOR THE WARRANTY PERIOD. ANY WARRANTED PART WHICH IS SCHEDULED FOR REPLACEMENT AS REQUIRED MAINTENANCE SHALL BE WARRANTED FOR THE PERIOD OF TIME UP TO THE FIRST SCHEDULED REPLACEMENT POINT FOR THE PART.

ANY REPLACEMENT PART THAT IS EQUIVALENT IN PERFORMANCE AND DULABILITY MAY BE USED IN NON-WARRANTY MAINTENANCE OR REPAIRS, AND SHALL NOT REDUCE THE WARRANTY OBLIGATION OF THE COMPANY.

THE COMPANY IS LIABLE FOR DAMAGES TO OTHER ENGINE COMPONENTS CAUSED BY THE FAILURE OF A WARRANTED PART STILL UNDER WARRANTY.

THE WARRANTY DOES NOT APPLY TO THOSE UNITS WHICH HAVE BEEN DAMAGED BY NEGLIGENCE OF INSTRUCTION LISTED IN THE OWNER/OPERATOR MANUAL FOR PROPER USE AND MAINTENANCE OF THE UNITS ACCIDENT MISHANDLING, ALTERATION, ABUSE, IMPROPER LUBRICATION, USE OF ANY PARTS OR ACCESSORIES OTHER THAN THOSE SPECIFIED BY THE COMPANY, OR OTHER CAUSES BEYOND THE COMPANY'S CONTROL.

THIS WARRANTY DOES NOT COVER THOSE PARTS REPLACED BY NORMAL WEAR OR HARMLESS CHANGES IN THEIR APPEARANCE.

THERE ARE NO OTHER EXPRESS WARRANTIES.

IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE **ARE LIMITED** TO TWO (2) YEARS OF HOME USE [ONE (1) YEAR FOR ANY OTHER USE] FROM THE ORIGINAL DELIVERY DATE.

LIABILITIES FOR INCIDENTAL OR CONSEQUENTIAL DAMAGE UNDER ANY AND ALL WARRANTIES ARE EXCLUDED.

IF YOU NEED TO OBTAIN MORE INFORMATION, PLEASE CALL YOUR NEAREST SERVICE CENTER, OR CHECK PLEASE KOMATSU ZENOAH WEB SITE http://www.zenoah.net